



QINGDAO RILI RUBBER CO., LTD  
TEL: +86-532-82301582 FAX:+86-532-84309130  
E-mail : [manager@rilirubber.com](mailto:manager@rilirubber.com)  
Factory Add: LIAOLAN TOWN, PINGDU CITY, QINGDAO, CHINA  
Website: [www.rilirubber.com](http://www.rilirubber.com)



**QINGDAO RILI RUBBER CO., LTD**

*Professional makes better*

## COMPANY PROFILE

QINGDAO RILI RUBBER CO., LTD Which was founded in 1999, Located in Qingdao, is one one the leading tyre factory in designing an manufacturing tyres in Shandong Province China.

As one of the largest manufacture, There are Light Truck tyres, OTR tyres, Mining tyres, Paddy tyres, Agricultural tyres, Forklift tyres, Seven big series, Including 80 kinds of specifications, more than 200 varieties of bias tyres. The Annual Output over 6 million sets.

To provide riders all over the world with the most superior quality tyres, RILI carries on total quality management in design, raw material, production, quality control, testing and check, logistics, after-sales services, etc. Nowadays, RILI tyre is contribute to bring safety, comfort and enjoyment to every driver in the world

Not only relying on advanced technology, world class production and testing equipment, but also the spirits to put the best possible tyres on the road and the desire to highest satisfy the driver's expectation. RILI tyres win recognition from customers and different international organizations. Nowadays, RILI tyres have got most certifications in the tyre industry including DOT, ECE, REACH, CCC, ISO9001, GCC, INMETRO, SASO, SONCAP, LATU, NOM, etc.

RILI pays much importance to brand culture and communication and takes personal training, serving and cooperate culture as the core stone as company cohesion and development. RILI not only works for the development of superior quality tyres, but also promotes social activities and charity events to help and support the society development.

The sole contact between the vehicle and the road is a patch of rubber. Drivers can only trust their trucks, buses or cars to turn, stop, and go if they trust their tyres. Aufine's passionate commitment to safety and performance inspires us to supply the best tyres for our customers. If there are vehicles, there are drivers, and as long as there are drivers, there will be RILI.

## CONTENTS

OFF -THE -ROAD TYRES .....	01-03
MINING MACHINE TYRE .....	03
AGRICULTURAL TYRE .....	04-10
LIGHT TRUCK BIAS TYRE .....	10-15
INDUSTRIAL TYRE .....	16-18
TRAILER TYRE .....	19-20

*Professional makes better*



# OFF THE ROAD TYRE



RH401



RH402

RH401/RH402		工程轮胎 OTR TYRE L3/E3					
规格 Size	层级 Ply	花纹编号 Pattern	外直径 Overall diameter MM	断面宽 Section width MM	标准轮辋 Standard rim	标准气压 Relevant Pressure Kpa	单胎负荷 Max Loading KG
7.50-16 TL/TTF	10	RH401	810	215	6.0	400	1900
8.25-16 TL/TTF	14	RH401	855	235	6.50H	630	1705
9.00-16 TL/TTF	12	RH401	885	222	7.5	300	2200
10.00-16 TL/TTF	12	RH401	895	233	7.5	300	2200
11.00-16 TL/TTF	12	RH401	860	240	7.5	300	2200
13.00-25TL/TTF	12	RH402	860	240	7.5	300	2200
14.00-24TL/TTF	12	RH402	1020	315	8.5	450	4125
14.00-24TL/TTF	24	RH401	1295	711	8.5	300	2720
14.00-24 TL/TTF	16	RH401	1370	375	11.0	375	4000
14.00-24 TL/TTF	24	RH401	1370	375	11.0	575	5150
14.00-24 TL/TTF	24	RH401	1370	375	10.0	575	5150
15.5-25 TL/TTF	20	RH401	1370	375	10.0	475	4625
16.00-24 TL/TTF	16	RH401	1370	375	10.0	375	4000
16.00-24 TL/TTF	12	RH401	1275	395	12.00/1.3	250	3250
16.00-24 TL/TTF	24	RH401	1490	430	11.3	475	6000
16.00-25 TL/TTF	20	RH401	1490	430	11.3	400	5450
16.00-25 TL/TTF	16	RH401	1490	430	11.3	325	4875
17.5-25 TL/TTF	24	RH401	1490	430	11.3	750	11500
18.00-25 TL/TTF	28	RH401	1490	430	11.3	875	12700
18.00-25 TL/TTF	16	RH401	1350	445	14/1.5	475	7300
20.5-25 TL/TTF	36	RH401	1615	495	13.0	850	16000
23.5-25 TL/TTF	32	RH401	1615	495	13.0	850	16000
23.5-25 TT/TTF	20	RH401	1490	520	17.00/2.0	450	9500
23.5-25 TL/TTF	20	RH401	1615	595	19.00/2.5	300	7300
26.5-25 TL/TTF	16	RH401	1615	595	19.5	225	6150
26.5-25 TL/TTF	24	RH401	1615	595	19.5	350	8000
29.5-25 TL/TTF	28	RH401	1743	645	22.00/3.0	350	10000
14/90-16 TT	24	RH401	1743	645	22.0	250	8250
16/70-20 TT	28	RH401	1850	750	22.00/3.0	325	11500
16/70-24 TTF	16	RH401	896	215	8.5H	290	1245
1200-16 TT	16	RH402	880	260	8.0	300	2200
1600-25 TL	16	RH401	1067	635	13.0	350	2600
1800-25 TL	16	RH401	1067	635	13.0	350	2600
11.00-16 TT/TL	12	RH401	884	244	8.5	390	1245
12.00-16 TT/TL	40	RH401	1490	430	11.3	875	12500
14/90-16 TT/TL	40	RH401	1615	500	13.0	850	16000

# OFF THE ROAD TYRE

RH408		工程轮胎 OTR TYRE L3/E3 NEW PATTERN					
规格 Size	层级 Ply	花纹编号 Pattern	外直径 Overall diameter MM	断面宽 Section width MM	标准轮辋 Standard rim	标准气压 Relevant Pressure Kpa	单胎负荷 Max Loading KG
825-16 TT/TL	14	RH408	867	235	6.5H	250 (50KM/H)	1900(10KM/H)
16/70-20 TT/TL	16	RH408	1075	410	13	400 (50KM/H)	3135(50KM/H)
20.5/70-16 TT/TL	14	RH408	920	353	13	280 (50KM/H)	1700(10KM/H)
17.5-25 TT/TL	16	RH408	1350	445	14.00/1.5	300	4250
20.5-25 TT/TL	20	RH408	1490	520	17.00/2.0	325	6000
23.5-25 TT/TL	20	RH408	1615	595	19.00/2.5	300	7300
26.5-25 TT/TL	28	RH408	1743	645	22.00/3.0	350	10000



RH408

RH435		工程轮胎 OTR GRANDERS TYRE G-2/L-2					
规格 Size	层级 Ply	花纹编号 Pattern	外直径 Overall diameter MM	断面宽 Section width MM	标准轮辋 Standard rim	标准气压 Relevant Pressure Kpa	单胎负荷 Max Loading KG
15.5-25 TL	12	RH435	1275	395	12.00/1.3	400	5600
17.5-25 TL	12	RH435	1350	445	14.00/1.5	350	6150
17.5-25 TL	16	RH435	1350	445	14.00/1.5	475	7300
17.5-25 TL	20	RH435	1350	445	14.00/1.5	575	8250
20.5-25 TL	16	RH435	1490	520	17.00/2.0	350	8250
23.5-25 TL	16	RH435	1615	595	19.5/2.5	300	9500
1300-24 TL	12	RH435	1280	330	8.00TQ	450	5600
1300-24 TL	16	RH435	1280	330	8.00TQ	525	6000
1400-24 TL	12	RH435	1350	360	8.00TQ	425	6300
1400-24 TL	16	RH435	1350	360	8.00TQ	550	7300



RH435

RH433		工程轮胎 OTR TYRE L-5					
规格 Size	层级 Ply	花纹编号 Pattern	外直径 Overall diameter MM	断面宽 Section width MM	标准轮辋 Standard rim	标准气压 Relevant Pressure Kpa	单胎负荷 Max Loading KG
17.5-25 TL/TT	16	RH433	1340	420	14.00/1.5	475	7300
20.5-25 TL/TT	20	RH433	1479	500	17.00/2.0	450	9500
23.5-25 TL/TT	20	RH433	1588	568	19.00/2.5	375	10900
26.5-25 TL/TT	28	RH433	1758	643	22.00/3.0	475	15500
29.5-25 TL/TT	28	RH433	1868	718	22.00/3.0	425	17500



RH433



## OFF THE ROAD TYRE



RH406

### RH406

#### 工程轮胎 E3-A

规格 Size	层级 Ply	花纹编号 Pattern	外直径 Overall diameter MM	断面宽 Section width MM	标准轮辋 Standard rim	标准气压 Relevant Pressure Kpa	单胎负荷 Max Loading KG
13.00-25 TL/TT	22	RH406	1300	350	10.00/15	550(50KM/H)	4250(50KM/H)



RH418

### RH418

#### 工程轮胎 E3-C

规格 Size	层级 Ply	花纹编号 Pattern	外直径 Overall diameter MM	断面宽 Section width MM	标准轮辋 Standard rim	标准气压 Relevant Pressure Kpa	单胎负荷 Max Loading KG
7.50-16 TL/TT	10	RH418	816	215	6	/	1900
8.25-16 TL/TT	14	RH418	867	235	6.5	/	1700
9.75-18 TL/TT	12	RH418	975	270	/	/	1700

## MINING MACHINE TYRE



RH502

### RH502

#### 矿山机械轮胎 MINING MACHINE TYRE

规格 Size	层级 Ply	花纹编号 Pattern	外直径 Overall diameter MM	断面宽 Section width MM	标准轮辋 Standard rim	标准气压 Relevant Pressure Kpa	单胎负荷 Max Loading KG
5.00-12 TL/TT	10	RH502	564	124	3.50B	500	560
5.50-13 TL/TT	10	RH502	618	140	4.00B	420	560
6.00-13 TL/TT	10	RH502	648	150	4.50B	420	650
6.00-14 TL/TT	14	RH502	675	150	4.5J	630	800
6.00-15 TL/TT	14	RH502	701	150	4.5E	630	825
6.50-16 TL/TT	14	RH502	753	162	5.50F	630	1060
7.00-16 TL/TT	16	RH502	780	176	5.50F	730	1320
7.50-16 TL/TT	18	RH502	812	190	6.00G	730	1500
8.25-16 TL/TT	18	RH502	855	205	6.50H	730	1800



RH806

### RH806

#### 矿山机械轮胎 MINING MACHINE TYRE

规格 Size	层级 Ply	花纹编号 Pattern	外直径 Overall diameter MM	断面宽 Section width MM	标准轮辋 Standard rim	标准气压 Relevant Pressure Kpa	单胎负荷 Max Loading KG
6.50-16 TL/TT	14	RH806	753	162	5.50F	630	1060
7.00-16 TL/TT	16	RH806	780	176	5.50F	730	1320
7.50-16 TL/TT	18	RH806	812	190	6.00G	730	1500
8.25-16 TL/TT	18	RH806	855	205	6.50H	730	1800

## AGRICULTURAL TYRE

### RH816

#### 农业轮胎 AGRICULTURAL TYRE R-1

规格 Size	层级 Ply	花纹编号 Pattern	外直径 Overall diameter MM	断面宽 Section width MM	标准轮辋 Standard rim	标准气压 Relevant Pressure Kpa	单胎负荷 Max Loading KG
4.00-8 TT	6	RH816	415	112	3.00D	300	265
5.00-12 TT	6	RH816	590	145	4.00E	200	280
5.50-17 TT	6	RH816	750	140	4.00E	520	780
6.00-12 TT	6	RH816	640	165	4.50E	250	405
6.00-14 TT	6	RH816	690	165	4.50E	250	450
6.00-16 TT	6	RH816	745	165	4.50E	250	495
6.50-16 TT	8	RH816	765	180	4.50E	250	565
7.50-16 TT	10	RH816	810	205	5.50F	210	650
7.50-20 TT	10	RH816	910	205	5.50F	210	760
8.30-20 TT	8	RH816	895	210	W7	240	695
8.30-24 TT	8	RH816	995	210	W7	240	810
9.50-20 TT	8	RH816	950	240	W8	280	955
9.50-24 TT	8	RH816	1050	240	W8	280	1110
11.2-24 TL/TT	10	RH816	1105	285	W10	300	1380
11.2-28 TT	6	RH816	1205	284	W10	180	1000
11.2-38 TT/TL	6	RH816	1420	260	W10	180	1150
1200-18 TT	12	RH816	1050	305	9.00V	420	2400
12-38 TT	8	RH816	1563	298	11	140	1570
12.4-24 TT	8	RH816	1159	315	W11	220	1285
12.4-24 TT	12	RH816	1159	315	W11	330	1600
12.4-28 TT	10	RH816	1260	315	W11	230	1510
12.4-38 TT	8	RH816	1514	315	W11	220	1600
12.4-38 TT	12	RH816	1514	315	W11	320	1850
13.6-24 TT	8	RH816	1210	345	W12	190	1400
13.6-24 TT	12	RH816	1210	345	W12	250	1700
13.6-28 TT	8	RH816	1311	345	W12	190	1500
13.6-28 TT	12	RH816	1311	345	W12	290	1910
13.6-38 TT	12	RH816	1565	345	W12	260	2000
13.6-38 TT	10	RH816	1548	328	W12	250	2215
14.9-24 TL	10	RH816	1265	378	W13	230	1990
14.9-26 TT	8	RH816	1316	378	W12	180	1650
14.9-26 TT	12	RH816	1316	378	W12	260	2060
14.9-28 TT	8	RH816	1367	378	W13	180	1760
14.9-28 TT	12	RH816	1367	378	W13	240	1950
14.9-30 TT	10	RH816	1415	378	W13	230	2190



RH816



RH816

## RH816

### 农业轮胎 AGRICULTURAL TYRE R-1

规格 Size	层级 Ply	花纹编号 Pattern	外直径 Overall diameter MM	断面宽 Section width MM	标准轮辋 Standard rim	标准气压 Relevant Pressure Kpa	单胎负荷 Max Loading KG
15-24 TT	10	RH816	1310	400	DW14	280	2800
15.5-38 TT	10	RH816	1570	395	DW14A	220	2000
15.5-38 TT	12	RH816	1570	395	DW14A	260	2500
16.9-24 TT	10	RH816	1333	429	W15L	190	2000
16.9-24 TT	12	RH816	1333	429	W15L	230	2120
16.9-28 TT	10	RH816	1435	429	W15L	190	2120
16.9-28 TT	12	RH816	1435	429	W15L	220	2360
16.9-30 TT	10	RH816	1485	430	W15L	190	2240
16.9-34 TT	10	RH816	1587	429	W15L	190	2360
16.9-34 TT	12	RH816	1587	429	W15L	230	2430
16.9-38 TT	10	RH816	1685	464	W15L	200	2760
18.4-26 TT	12	RH816	1450	467	DW16A	220	2650
18.4-26 TT	16	RH816	1450	467	DW16A	250	2900
18.4-30 TT	10	RH816	1550	467	W16L	180	2500
18.4-30 TT	12	RH816	1550	467	W16L	220	2900
18.4-34 TT	10	RH816	1654	467	W16L	180	2725
18.4-34 TT	12	RH816	1654	467	W16L	220	3075
18.4-34 TT	14	RH816	1654	467	W16L	250	3250
18.4-38 TT	10	RH816	1755	467	W16A	180	2900
18.4-38 TT	12	RH816	1755	467	W16A	220	3250
18.4-42 TT	10	RH816	1857	467	W16	180	3330
20.8-38 TT	10	RH816	1834	528	W18A	150	3150
20.8-38 TT	12	RH816	1834	528	W18A	190	3550
23.1-26 TT	12	RH816	1605	587	DW20A	170	3250
23.1-26 TT	16	RH816	1605	587	DW20A	220	3750
23.1-30 TT	12	RH816	1707	587	DW20A	170	3450
23.1-30 TT	16	RH816	1707	587	DW20A	225	4000
24.5-32 TT	12	RH816	1803	622	DW21A	170	4000
675/175-12 TT	8	RH816	640	165	4.50E	250	405



RH660

## RH660

### 农业轮胎 INDUSTRIAL TRACTOR F-3

规格 Size	层级 Ply	花纹编号 Pattern	外直径 Overall diameter MM	断面宽 Section width MM	标准轮辋 Standard rim	标准气压 Relevant Pressure Kpa	单胎负荷 Max Loading KG
11L-15 TL	10	RH660	813	279	8LB	360	1060
11L-16 TL	12	RH660	838	279	8LB	440	1250

## RH880

### 农业轮胎 FARM TYRE F-2

规格 Size	层级 Ply	花纹编号 Pattern	外直径 Overall diameter MM	断面宽 Section width MM	标准轮辋 Standard rim	标准气压 Relevant Pressure Kpa	单胎负荷 Max Loading KG
6.50-20 TT/TL	10	RH880	860	180	5.00F	585	880
4.00-16 TT/TL	8	RH880	655	122	3.00D	360	615
4.00-14 TT/TL	6	RH880	590	110	3.00D	255	405
4.00-12 TT/TL	4	RH880	535	110	3.00D	340	250
4.00-19 TT/TL	4	RH880	720	110	3.00D	360	325
5.00-15 TT/TL	4	RH880	665	140	4J	300	325
5.00-16 TT/TL	6	RH880	665	150	4.00E	390	475
5.50-16 TT/TL	8	RH880	710	150	4.00E	370	530
6.00-16 TT/TL	8	RH880	740	160	4.00E	450	675
6.50-16 TT/TL	8	RH880	750	175	4.50E	420	735
7.5L-15 TT/TL	8	RH880	745	208	6LB	330	750
7.50-16 TT/TL	8	RH880	810	205	5.50F	390	775
7.50-18 TT/TL	8	RH880	860	205	5.50F	390	850
7.50-20 TT/TL	8	RH880	910	205	5.50F	370	1020
9.5L-15 TT/TL	8	RH880	780	240	8LB	330	850
11L-15 TT/TL	8	RH880	810	280	8LB	300	950
9.00-16 TT/TL	8	RH880	890	245	W7L	400	1200
10.00-16 TT/TL	10	RH880/RH881	910	275	W8L	360	1120
11.00-16 TT/TL	10	RH880/RH881	970	315	W10L	330	1320
10-15 TT/TL	8	RH880	855	276	8LB	240	1425



RH880



RH881

## RH884

### 农业轮胎 IMPLEMENT & TRAILER TYRE RH884

规格 Size	层级 Ply	花纹编号 Pattern	外直径 Overall diameter MM	断面宽 Section width MM	标准轮辋 Standard rim	标准气压 Relevant Pressure Kpa	单胎负荷 Max Loading KG
10.0/80-12 TL	8	RH884	710	264	9	390	1250
10.0/75-15.3 TL	10	RH884	760	264	9	390	1525
11.5/80-15.3 TL	12	RH884	865	290	9	410	2145
12.5/80-15.3 TL	14	RH884	875	307	9	510	2810
13.0/65-18 TL	14	RH884	890	336	11	430	2575



RH884





RH885

RH885		农业轮胎 IMPLEMENT TYRE I-1					
规格 Size	层级 Ply	花纹编号 Pattern	外直径 Overall diameter MM	断面宽 Section width MM	标准轮辋 Standard rim	标准气压 Relevant Pressure Kpa	单胎负荷 Max Loading KG
650-16 TT/TL	10	RH885	735	173	4.50E	410	920
750-16 TT/TL	10	RH885	788	211	5.50F	410	1215
900-16 TT/TL	10	RH885	848	234	6LB	360	1500
95L-15 TT/TL	8	RH885	767	241	8LB	300	1120
95L-14 TT/TL	8	RH885	741	241	8LB	300	1090
105/80-18 TT/TL	12	RH885	885	276	9	410	1950
11L-15 TT/TL	8	RH885	777	279	8LB	250	1150
11L-15 TT/TL	12	RH885	777	279	8LB	360	1450
11L-14 TT/TL	8	RH885	752	279	8LB	250	1100
11L-16 TT/TL	8	RH885	803	279	8LB	250	1215
125L-15 TT/TL	12	RH885	823	318	10LB	250	1145
760L-15 TT/TL	8	RH885	734	193	6LB	360	950



RH669

RH669		农业轮胎 FORESTRY TIRES					
规格 Size	层级 Ply	花纹编号 Pattern	外直径 Overall diameter MM	断面宽 Section width MM	标准轮辋 Standard rim	标准气压 Relevant Pressure Kpa	单胎负荷 Max Loading KG
28L-26-16 TL/TT	16	RH669	1620	715	DW25	210	4750
305L-32-18 TL/TT	18	RH669	1845	715	DH27	210	5950



RH882

RH882		农业轮胎 AGRICULTURAL TIRES R-2					
规格 Size	层级 Ply	花纹编号 Pattern	外直径 Overall diameter MM	断面宽 Section width MM	标准轮辋 Standard rim	标准气压 Relevant Pressure Kpa	单胎负荷 Max Loading KG
14.9-24 TT	8	RH882	1305	378	W13	180	1600
14.9-28 TT	8	RH882	1406	378	W13	180	1700
16.9-34 TT	10	RH882	1585	430	W15	190	2360
18.4-30 TT	10	RH882	1550	467	W16L	180	2500
18.4-34 TT	10	RH882	1655	467	W16L	180	2725
18.4-38 TT	10	RH882	1755	467	W16L	180	2900
23.1-26 TT	12	RH882	1605	587	DW20	170	3250
23.1-26 TT	16	RH882	1605	587	DW20	220	3750
23.1-30 TT	12	RH882	1829	610	DW20	170	3450
23.1-30 TT	16	RH882	1829	610	DW20	225	4000

RH801		农业轮胎					
规格 Size	层级 Ply	花纹编号 Pattern	外直径 Overall diameter MM	断面宽 Section width MM	标准轮辋 Standard rim	标准气压 Relevant Pressure Kpa	单胎负荷 Max Loading KG
4.00-8 TT	6	RH801	425	110	3.00D	340	180
4.00-12 TT	6	RH801	535	110	3.00D	340	250
4.00-14 TT	8	RH801	590	110	3.00D	340	270
4.00-16 TT	8	RH801	640	110	3.00D	340	300
4.50-14 TT	8	RH801	605	122	3.00D	426	680
4.50-16 TT	8	RH801	655	122	3.00D	360	615
5.00-14 TT	10	RH801	620	130	3.00D	420	500
5.00-16 TT	10	RH801	655	130	4.00E	500	650
5.50-16 TT	10	RH801	685	150	4.00E	500	800
6.00-16 TT	10	RH801	740	160	4.50E	450	675
6.50-16 TT	12	RH801	760	175	5.50F	420	735
7.50-16 TT	16	RH801	785	203	5.50F	400	1240
7.50-20 TT	14	RH801	910	205	5.50F	370	1020



RH801

RH856		农业轮胎					
规格 Size	层级 Ply	花纹编号 Pattern	外直径 Overall diameter MM	断面宽 Section width MM	标准轮辋 Standard rim	标准气压 Relevant Pressure Kpa	单胎负荷 Max Loading KG
4.50-14 TT	8	RH856	606	122	3.00D	420	592
4.5-16 TT	8	RH856	655	122	3.00D	360	615
5.00-16 TT	10	RH856	655	130	4.00E	500	650
5.50-16 TT	10	RH856	685	150	4.00E	500	800



RH856

RH815		农业轮胎					
规格 Size	层级 Ply	花纹编号 Pattern	外直径 Overall diameter MM	断面宽 Section width MM	标准轮辋 Standard rim	标准气压 Relevant Pressure Kpa	单胎负荷 Max Loading KG
650-16 TT	14	RH815	765	173	5.00F	275	775



RH815

# AGRICULTURAL TYRE



RH665



RH663



RH664



RH667



RH668

## RH665

### 农业轮胎 FLOATION TIRES I-3

规格 Size	层级 Ply	花纹编号 Pattern	外直径 Overall diameter MM	断面宽 Section width MM	标准轮辋 Standard rim	标准气压 Relevant Pressure Kpa	单胎负荷 Max Loading KG
400/60-15.5 TL	14	RH665	874	400	13.00	360	2900
550/45-22.5 TL	16	RH665	1067	533	16.00	280	4375
600/50-22.5 TL	16	RH665	1170	610	20.00	260	5150
600/50-22.5 TL	18	RH665	1170	610	20.00	290	5600

## RH663/RH664

### 农业轮胎 FLOATION TIRES I-3

规格 Size	层级 Ply	花纹编号 Pattern	外直径 Overall diameter MM	断面宽 Section width MM	标准轮辋 Standard rim	标准气压 Relevant Pressure Kpa	单胎负荷 Max Loading KG
15.5/65-18 TL	10	RH664	915	395	W13	350	2300
18.0-15.5 TL	10	RH663	980	450	13.00	350	4185

## RH667

### 农业轮胎 FLOATION TIRES I-3

规格 Size	层级 Ply	花纹编号 Pattern	外直径 Overall diameter MM	断面宽 Section width MM	标准轮辋 Standard rim	标准气压 Relevant Pressure Kpa	单胎负荷 Max Loading KG
26X12-12 TL	8	RH667	648	307	10.50I	140	810
31X15.5-15 TL	8	RH667	792	391	13.00	310	1250

## RH668

### 农业轮胎 FLOATION TIRES I-3

规格 Size	层级 Ply	花纹编号 Pattern	外直径 Overall diameter MM	断面宽 Section width MM	标准轮辋 Standard rim	标准气压 Relevant Pressure Kpa	单胎负荷 Max Loading KG
405/70-20 TL	14	RH668	1076	407	13.00	350	3250
405/70-24 TL	14	RH668	1178	407	13.00	350	3550

# AGRICULTURAL TYRE

## RH607

### 水田轮胎 PADDY FIELD SPECIAL TYRE

规格 Size	层级 Ply	花纹编号 Pattern	外直径 Overall diameter MM	断面宽 Section width MM	标准轮辋 Standard rim	标准气压 Relevant Pressure Kpa	单胎负荷 Max Loading KG
6.00-12 TT	8	RH607	690	165	4.50E	270	425
6.00-14 TT	8	RH607	740	165	4.50E	250	450
6.5-16 TT	6	RH607	813	165	5.00F	250	565
7.50-16 TT	8	RH607	889	203.2	5.50F	210	650
8.3-20 TT	8	RH607	950	203.2	W7	270	970
8.3-24 TT	8	RH607	1041	180	4.50E	270	1135
9.5-24 TT	8	RH607	1143	230	W8	310	1420
11.2-24 TT	8	RH607	1194	280	W10	210	1465
11-32 TT	10	RH607	1448	305	W10	160	1080
12.4-28 TT	8	RH607	1320	305	W11	200	1785
14.9-24 TT	10	RH607	1347	378	W13	270	2290
13.6-38 TT	10	RH607	1700	330	W12	250	2780
16.9-34 TT	10	RH607	1651	406	W15L	220	3385



RH607

# LIGHT TRUCK BIAS TYRE

## RH811

### 轻型载重汽车轮胎 LIGHT TRUCK BIAS TYRE

规格 Size	层级 Ply	花纹编号 Pattern	外直径 Overall diameter MM	断面宽 Section width MM	标准轮辋 Standard rim	标准气压 Relevant Pressure Kpa	单胎负荷 Max Loading KG
450-12 TL/TTF	8	RH811	545	127	3.00B	400	412
500-12 TL/TTF	8	RH811	568	143	3.50B	400	487
650-15 TL/TTF	12	RH811	730	180	4.50E	530	950
650-16 TL/TTF	12	RH811	750	185	5.50F	630	1060
700-15 TL/TTF	12	RH811	750	200	5.50F	630	1150
700-16 TL/TTF	14	RH811	775	200	5.50F	730	1320
750-16 TL/TTF	16	RH811	805	215	6.00G	730	1500



RH811



# LIGHT TRUCK BIAS TYRE



RH812

## RH812

### 轻型载重汽车轮胎 LIGHT TRUCK BIAS TYRE

规格 Size	层级 Ply	花纹编号 Pattern	外直径 Overall diameter MM	断面宽 Section width MM	标准轮辋 Standard rim	标准气压 Relevant Pressure Kpa	单胎负荷 Max Loading KG
4.00-8 TL/TTF	6	RH812	415	112	3.00D	300	265
4.50-12 TL/TTF	8	RH812	545	127	3.00B	400	412
4.50-14 TL/TTF	8	RH812	606	122	3.00D	420	592
5.00-14 TL/TTF	10	RH812	620	130	3.00D	500	600
5.50-13 TL/TTF	10	RH812	620	160	4.00B	420	560
6.00-13 TL/TTF	10	RH812	655	170	4.50B	420	650
6.00-14 TL/TTF	10	RH812	680	170	4.50B	530	800
6.00-15 TL/TTF	10	RH812	705	170	4.50E	530	825
6.50-16 TL/TTF	12	RH812	750	185	5.50F	630	1060
7.00-16 TL/TTF	14	RH812	775	200	5.50F	730	1320
7.50-16 TL/TTF	16	RH812	805	215	6.00G	730	1500

## RH869

### 轻型载重汽车轮胎 LIGHT TRUCK BIAS TYRE

规格 Size	层级 Ply	花纹编号 Pattern	外直径 Overall diameter MM	断面宽 Section width MM	标准轮辋 Standard rim	标准气压 Relevant Pressure Kpa	单胎负荷 Max Loading KG
6.00-13 TL/TTF	8	RH869	655	170	4.50B	320	560
6.00-14 TL/TTF	10	RH869	680	170	4.5J	530	800
6.50-14 TL/TTF	10	RH869	705	180	4.5J	530	900
6.00-15 TL/TTF	10	RH869	705	170	4.50E	530	825
6.50-16 TL/TTF	12	RH869	750	185	5.50F	630	1060
7.00-16 TL/TTF	14	RH869	775	200	5.50F	730	1320
7.50-16 TL/TTF	16	RH869	805	215	6.00G	730	1500
8.25-16 TL/TTF	18	RH869	855	235	6.50H	730	1800
8.25-20 TL/TTF	14	RH869	974	235	6.50H	810	2205
9.00-20 TL/TTF	14	RH869	1018	259	7	770	2575
10.00-20 TL/TTF	16	RH869	1055	278	7.5	810	3000
11.00-22 TL/TTF	18	RH869	1130	293	8	910	3830
11.00-20 TL/TTF	16	RH869	1085	293	8	810	3270
12.00-24 TL/TTF	18	RH869	1225	315	8.5	810	4195
12.00-20 TL/TTF	18	RH869	1125	315	8.5	810	3730



RH869

# LIGHT TRUCK BIAS TYRE



RH866

## RH866

### 轻型载重汽车轮胎 LIGHT TRUCK BIAS TYRE

规格 Size	层级 Ply	花纹编号 Pattern	外直径 Overall diameter MM	断面宽 Section width MM	标准轮辋 Standard rim	标准气压 Relevant Pressure Kpa	单胎负荷 Max Loading KG
4.00-8 TL/TTF	6	RH866	415	112	3.00D	300	265
4.00-12 TL/TTF	6	RH866	535	110	3.00D	340	250
4.00-14 TL/TTF	8	RH866	590	110	3.00D	340	270
4.00-16 TL/TTF	8	RH866	640	110	3.00D	340	300
4.50-16 TL/TTF	8	RH866	655	122	3.00D	360	615
5.00-14 TL/TTF	10	RH866	620	130	3.00D	420	500
5.00-16 TL/TTF	10	RH866	655	130	4.00E	500	650
5.50-16 TL/TTF	10	RH866	685	150	4.00E	500	800
6.00-13 TL/TTF	10	RH866	655	170	4.50B	420	650
6.00-14 TL/TTF	10	RH866	680	170	4.50J	530	800
6.00-15 TL/TTF	10	RH866	705	170	4.50E	530	825
6.00-16 TL/TTF	10	RH866	730	170	4.50E	530	850
6.50-14 TL/TTF	10	RH866	705	180	4.50J	530	900
6.50-16 TL/TTF	12	RH866	750	185	5.50F	630	1060
7.00-16 TL/TTF	14	RH866	775	200	5.50F	730	1320
7.00-20 TL/TTF	14	RH866	904	200	5.5	840	1750
7.50-16 TL/TTF	16	RH866	805	215	6.00G	730	1500
7.50-20 TL/TTF	14	RH866	935	215	6	810	1900
8.25-16 TL/TTF	18	RH866	855	235	6.50H	730	1800

## RH888

### 轻型载重汽车轮胎 LIGHT TRUCK BIAS TYRE

规格 Size	层级 Ply	花纹编号 Pattern	外直径 Overall diameter MM	断面宽 Section width MM	标准轮辋 Standard rim	标准气压 Relevant Pressure Kpa	单胎负荷 Max Loading KG
5.00-12 TL/TTF	10	RH888	568	143	3.50B	500	560
5.50-13 TL/TTF	8	RH888	620	160	4.00B	420	560
6.00-13 TL/TTF	10	RH888	655	170	4.50B	420	650
6.00-14 TL/TTF	12	RH888	680	170	4.5J	630	800
6.00-15 TL/TTF	12	RH888	705	170	4.50E	630	1060
6.50-16 TL/TTF	12	RH888	750	185	5.50F	630	860
7.00-16 TL/TTF	14	RH888	775	200	5.50F	730	1320
7.50-16 TL/TTF	18	RH888	812	190	6.00G	630	1045
8.25-16 TL/TTF	18	RH888	855	205	6.50H	730	1800



RH888



# LIGHT TRUCK BIAS TYRE



RH110

规格		层级	花纹编号	外直径	断面宽	标准轮辋	标准气压	单胎负荷
Size	Ply	Pattern	Overall diameter MM	Section width MM	Standard rim	Relevant Pressure Kpa	Max Loading KG	
1400-20 TL/TTF	18	RH110	1240	375	10	600	4000	



RH111

规格		层级	花纹编号	外直径	断面宽	标准轮辋	标准气压	单胎负荷
Size	Ply	Pattern	Overall diameter MM	Section width MM	Standard rim	Relevant Pressure Kpa	Max Loading KG	
1200-24 TL/TTF	18	RH111	1225	350	8.5	810	4195	
1200-20 TL/TTF	18	RH111	1125	350	7.5	810	3730	
1000-20 TL/TTF	16	RH111	1055	278	7.5	810	3000	
8.25-16 TL/TTF	16	RH111	855	235	6.50H	630	1705	
7.50-16 TL/TTF	16	RH111	805	215	6.00G	730	1500	
7.00-16 TL/TTF	14	RH111	775	200	5.50F	630	1220	
6.50-16 TL/TTF	10	RH111	750	185	5.50F	530	975	



RH115

规格		层级	花纹编号	外直径	断面宽	标准轮辋	双胎最大负荷	单胎负荷	双胎气压	单胎气压
Size	Ply	Pattern	Overall diameter MM	Section width MM	Standard rim	LOAD DUAL KG	Max Loading KG	DUAL PRESSURE KPA	SINGLE PRESSURE KPA	
7.5-16 TL/TTF	14	RH115	815	215	6.00G	1320	1500	700	730	



RH116

规格		层级	花纹编号	外直径	断面宽	标准轮辋	双胎最大负荷	单胎负荷	双胎气压	单胎气压
Size	Ply	Pattern	Overall diameter MM	Section width MM	Standard rim	LOAD DUAL KG	Max Loading KG	DUAL PRESSURE KPA	SINGLE PRESSURE KPA	
8.25-16 TL/TTF	14	RH116	867	235	6.50H	1500	1700	600	630	
7.50-16 TL/TTF	14	RH116	815	215	6.00G	1320	1500	700	730	
7.00-16 TL/TTF	12	RH116	785	200	5.50F	1060	1215	600	630	

# LIGHT TRUCK BIAS TYRE



RH118

规格		层级	花纹编号	外直径	断面宽	标准轮辋	双胎最大负荷	单胎负荷	双胎气压	单胎气压
Size	Ply	Pattern	Overall diameter MM	Section width MM	Standard rim	LOAD DUAL KG	Max Loading KG	DUAL PRESSURE KPA	SINGLE PRESSURE KPA	
1200-24 TL/TTF	18	RH118	1225	315	8.5	3680	4195	740	810	
1200-20 TL/TTF	18	RH118	1125	315	8.5	3270	3730	740	810	
1100-22 TL/TTF	18	RH118	1130	293	8	3410	3830	810	910	
1100-20 TL/TTF	16	RH118	1085	293	8	2780	3270	740	810	
1000-20 TL/TTF	16	RH118	1055	278	7.5	2630	3000	740	810	
900-20 TL/TTF	14	RH118	1018	259	7	2255	2575	700	770	
8.25-20 TL/TTF	14	RH118	974	235	6.50H	1940	2205	740	810	
7.50-16 TL/TTF	16	RH118	805	215	6.00G	1320	1500	730	730	
7.00-16 TL/TTF	14	RH118	775	200	5.50F	1075	1220	630	630	
6.50-16 TL/TTF	10	RH118	750	185	5.50F	860	975	530	530	



RH119

规格		层级	花纹编号	外直径	断面宽	标准轮辋	双胎最大负荷	单胎负荷	双胎气压	单胎气压
Size	Ply	Pattern	Overall diameter MM	Section width MM	Standard rim	LOAD DUAL KG	Max Loading KG	DUAL PRESSURE KPA	SINGLE PRESSURE KPA	
500-12 TL/TTF	8	RH119	582	154	3.50B	462	487	400	400	
700-20 TL/TTF	12	RH119	904	200	5.5	1385	1580	670	640	
700-16 TL/TTF	14	RH119	775	200	5.50F	1075	1220	630	630	
7.50-20 TL/TTF	14	RH119	935	215	6	1655	1885	740	810	
7.50-16 TL/TTF	16	RH119	805	215	6.00G	1320	1500	730	730	
8.25-16 TL/TTF	16	RH119	855	235	6.50H	1500	1705	630	630	
900-16 TL/TTF	14	RH119	890	255	6.50H	1720	1955	630	630	



RH220

规格		层级	花纹编号	外直径	断面宽	标准轮辋	双胎最大负荷	单胎负荷	相应气压
Size	Ply	Pattern	Overall diameter MM	Section width MM	Standard rim	LOAD DUAL KG	Max Loading KG	PRESSURE KPA	
7.50-15 TL/TTF	12	RH220	808	215	6	1210	1307	630	
7.00-15 TL/TTF	10	RH220	750	200	5.50F	915	1040	530	
6.50-15 TL/TTF	8	RH220	730	180	4.50E	720	820	420	
6.50-14 TL/TTF	8	RH220	730	180	4.50E	690	785	420	
6.00-15 TL/TTF	8	RH220	705	170	4.50E	630	702	420	
6.00-14 TL/TTF	8	RH220	680	170	4.1/2J	600	685	420	
6.00-13 TL/TTF	8	RH220	655	170	4.1/2J	570	655	420	
5.50-13 TL/TTF	8	RH220	620	160	4J	500	565	420	
5.00-12 TL/TTF	8	RH220	582	154	3.50B	462	487	400	

## LIGHT TRUCK BIAS TYRE



RH221

规格 Size		层级 Ply	花纹编号 Pattern	外直径 Overall diameter MM	断面宽 Section width MM	标准轮辋 Standard rim	双胎最大负荷 LOAD DUAL KG	单胎负荷 Max Loading KG	双胎气压 DUAL PRESSURE KPA	单胎气压 SINGLE PRESSURE KPA
7.00-15 TL/TTF		10	RH221	750	200	5.50F	915	1040	530	530
6.50-16 TL/TTF		10	RH221	750	185	5.50F	860	975	530	530
6.50-14 TL/TTF		8	RH221	705	180	41/2J	690	785	420	420
6.00-16 TL/TTF		10	RH221	710	158	4.50E	755	860	530	530
6.00-15 TL/TTF		8	RH221	705	170	4.5E	630	720	420	420
6.00-14 TL/TTF		8	RH221	680	170	41/2J	600	685	420	420
6.00-13 TL/TTF		8	RH221	655	170	41/2J	570	655	420	420



RH222

规格 Size		层级 Ply	花纹编号 Pattern	外直径 Overall diameter MM	断面宽 Section width MM	标准轮辋 Standard rim	相应气压 Relevant Pressure Kpa	最大负荷 Max Loading KG
9.00-17 TL/TTF		8	RH222	856	225	17INCH	310	1320
9.00-16 TL/TTF		8	RH222	834	225	16INCH	310	1360
14.00-20 TL/TTF		18	RH222	1215	330	10.0	425	3270



RH113

规格 Size		层级 Ply	花纹编号 Pattern	外直径 Overall diameter MM	断面宽 Section width MM	标准轮辋 Standard rim	标准气压 Relevant Pressure Kpa	单胎负荷 Max Loading KG
12.00-20 TL/TTF		20	RH113	1130	310	8.0	790	6335

## INDUSTRIAL TYRE

规格 Size		层级 Ply	花纹编号 Pattern	外直径 Overall diameter MM	断面宽 Section width MM	标准轮辋 Standard rim	标准气压 Relevant Pressure Kpa	单胎负荷 Max Loading KG
4.00-8 TTF		8	RH302	422	108	2.50C	960	690
5.00-8 TTF		10	RH302	469	131	3.00D	1000	1290
6.00-9 TTF		10	RH302	540	160	4.00E	860	1415
6.50-10 TTF		12	RH302	590	178	5.00F	970	2170
7.00-9 TTF		10	RH302	590	190	5.00S	850	1865
7.00-12 TTF		12	RH302	676	192	5.00S	860	2720
7.50-15 TTF		12	RH302	798	215	6.00G	790	3490
8.25-12 TTF		12	RH302	728	210	5.00S	695	2000
8.25-15 TTF		14	RH302	834	236	6.5	720	3935
18x7-8 TTF		14	RH302	465	173	4.33	900	1440
28x9-15 TTF		14	RH302	684	221	7.00BD	930	4255
29x8-15 TTF		12	RH302	710	220	5.5	860	3150
10.00-20 TTF		16	RH338	1055	278	7.5	790	6765
12.00-20 TTF		20	RH338	1125	315	8.5	965	8970



RH302



RH338

规格 Size		层级 Ply	花纹编号 Pattern	外直径 Overall diameter MM	断面宽 Section width MM	标准轮辋 Standard rim	标准气压 Relevant Pressure Kpa	单胎负荷 Max Loading KG
10.5/80-18 TL		10	RH316	885	274	9.00	370	1935
12.5/80-18 TL		12	RH316	965	308	9.00	370	2625



RH316

规格 Size		层级 Ply	花纹编号 Pattern	外直径 Overall diameter MM	断面宽 Section width MM	标准轮辋 Standard rim	标准气压 Relevant Pressure Kpa	单胎负荷 Max Loading KG
16.9-24 TL		12	RH308	1265	378	W13	230	1990
16.9-28 TL		12	RH308	1435	430	DW15	260	3450
17.5L-24 TL		12	RH308	1241	445	DW15L	190	1725
18.4-26 TL		12	RH308	1426	467	DW16A	250	3875
18.4-26 TL		16	RH308	1426	467	DW16A	300	4000
19.5L-24 TL		12	RH308	1314	495	DW17L	210	2145
21L-24 TL		12	RH308	1402	533	DW18A	220	3875



RH308





**RH330**



**RH331**



**RH332**



**RH334**



**RH335**



**RH337**

## RH330/RH331/RH332/RH334/RH335/RH337

规格 Size	层级 Ply	花纹编号 Pattern	外直径 Overall diameter MM	断面宽 Section width MM	标准轮辋 Standard rim	标准气压 Relevant Pressure Kpa	单胎负荷 Max Loading KG
10-16.5 TL	10	RH330	795	264	8.25	620	2375
12-16.5 TL	12	RH330	831	320	9.75	550	2865
10-16.5 TL	10	RH331	775	264	8.25	520	2135
12-16.5 TL	12	RH331	831	320	9.75	550	2865
14-17.5 TL	14	RH331	922	351	10.5	550	3875
15-19.5 TL	14	RH331	1029	391	11.75	485	4565
23x8.5-12 TL	6	RH331	574	213	7.00I	240	820
27x8.5-15 TL	6	RH331	691	259	8.5	310	1080
27x10.5-15 TL	6	RH331	678	213	7JA	310	1030
10-16.5 TL	12	RH332	773	264	8.25	620	2375
12-16.5 TL	14	RH332	835	307	9.75	620	3075
10-16.5 TL	12	RH334	795	279	8.25	520	2140
12-16.5 TL	14	RH334	835	325	9.75	550	2885
10-16.5 TL	12	RH335	773	264	8.25	520	2135
12-16.5 TL	14	RH335	831	307	9.75	550	2865
10-16.5 TL	10	RH337	820	264	8.25	520	1930
12-16.5 TL	12	RH337	831	325	9.75	550	2865

## RH771/RH772

### 工业轮胎 INDUSTRIAL TRACTORS TYRE

规格 Size	层级 Ply	花纹编号 Pattern	外直径 Overall diameter MM	断面宽 Section width MM	标准轮辋 Standard rim	标准气压 Relevant Pressure Kpa	单胎负荷 Max Loading KG
19.5L-24 TL	12	RH771	1314	495	DW17L	230	3455
19.5L-24 TL	12	RH772	1314	495	DW17L	230	3455



**RH771**

## RH773

### 工业轮胎 EXCAVATOR TYRE

规格 Size	层级 Ply	花纹编号 Pattern	外直径 Overall diameter MM	断面宽 Section width MM	标准轮辋 Standard rim	标准气压 Relevant Pressure Kpa	单胎负荷 Max Loading KG
8.25-20 TTF	14	RH773	992	245	6.5	675	2060
9.00-20 TTF	14	RH773	1030	260	7	700	3000
10.00-20 TTF	16	RH773	1062	280	7.5	810	3000



**RH772**

## RH994

### 工业车实心轮胎 INDUSTRIAL SOLID TYRES

规格 Size	标准轮辋 S.R	外直径 OD	断面宽 SW	最大负荷 MAX LOAD>			
				10KM/H		26KM/H	
			载重LOAD	气压ROTA	载重LOAD	气压ROTA	
300-15(315/70-15)	8	838	258	5990	4700	5380	4037



**RH773**



**RH994**

# TRAILER TYRE



RH550

RH550			拖车轮胎 TRAILER TYRE				
SIZE	PLY	PATTERN	RIM WIDTH INCH	OVERALL DIAMETER MM	SECTION WIDTH MM	MAX LOAD (LBS)	PSI
ST175/80D13 TL	6PR	RH550	5.00	610	177	1360	50
ST205/75D14 TL	6PR	RH550	5.50	664	203	1760	50
ST205/75D15 TL	6PR	RH550	5.50	689	203	1820	50
ST225/75D15 TL	8PR	RH550	6.00	719	223	2540	65
ST235/80D16TL	10PR	RH550	6.50	782	235	3640	80



RH551

RH551/RH555			拖车轮胎 TRAILER TYRE				
SIZE	PLY	PATTERN	RIM WIDTH INCH	OVERALL DIAMETER MM	SECTION WIDTH MM	MAX LOAD (LBS)	PSI
7.00-15 TL	10PR	RH551/RH555	5.50	752	202	2910	80
7.50-16TL	10PR	RH551/RH555	6.00	808	220	3520	80



RH552

RH552			拖车轮胎 TRAILER TYRE				
SIZE	PLY	PATTERN	RIM WIDTH INCH	OVERALL DIAMETER MM	SECTION WIDTH MM	MAX LOAD (LBS)	PSI
8-14.5 TL	14PR	RH552	6.00	707	203	3040	115



RH555

# TRAILER TYRE



RH556

RH556			拖车轮胎 TRAILER TYRE				
SIZE	PLY	PATTERN	RIM WIDTH INCH	OVERALL DIAMETER MM	SECTION WIDTH MM	MAX LOAD (LBS)	PSI
4.80-8 TL	4	RH556	3.75	423	121	585	60
4.80-8 TL	6	RH556	3.75	423	121	760	90
5.70-8 TL	4	RH556	4.50	469	146	715	50
5.70-8 TL	6	RH556	4.50	469	146	910	75
5.70-8 TL	8	RH556	4.50	469	146	1070	100
4.80-12 TL	4	RH556	3.75	524	121	785	60
4.80-12 TL	6	RH556	3.75	524	121	990	90
5.30-12 TL	4	RH556	4.25	548	135	855	55
5.30-12 TL	6	RH556	4.25	548	135	910	80
5.30-12 TL	8	RH556	4.25	548	135	1140	90

RH559			拖车轮胎 TRAILER TYRE				
SIZE	PLY	PATTERN	RIM WIDTH INCH	OVERALL DIAMETER MM	SECTION WIDTH MM	MAX LOAD (LBS)	PSI
16.5x6.5-8 TL	4	RH559	5.375	411	165	615	45
16.5x6.5-8 TL	6	RH559	5.375	411	165	785	70
16.5x6.5-8 TL	8	RH559	5.375	411	165	910	90
18.5x8.5-8 TL	4	RH559	7.00	462	213	760	35
18.5x8.5-8 TL	6	RH559	7.00	462	213	935	50
18.5x8.5-8 TL	8	RH559	7.00	462	213	1070	65
20.5x8.0-10 TL	4	RH559	6.00	518	203	910	35
20.5x8.0-10 TL	6	RH559	6.00	518	203	1100	50
20.5x8.0-10 TL	8	RH559	6.00	518	203	1320	70
20.5x8.0-10 TL	10	RH559	6.00	518	203	1520	90



RH559

RH557/RH558			拖车轮胎 TRAILER TYRE				
SIZE	PLY	PATTERN	RIM WIDTH INCH	OVERALL DIAMETER MM	SECTION WIDTH MM	MAX LOAD (LBS)	PSI
10.00-20 TTF	14PR	RH557	7.50	1055	254	5730	90
11-22.5 TL	14PR	RH558	8.25	1054.00	279	6175	100



RH557



RH558